

# DECLARATION OF CONFORMITY

The undersigned, representing  
Thermory AS  
hereby declares that the

**Thermally modified solid wood radiata pine paneling  
without surface coating**

is in conformity with the provisions of the EC Directive 89/106/EEC and 93/68/EEC  
when used as solid wood paneling according to Annex ZA of

**EN 14915:2013 + A1:2017**

CHARACTERISTIC	PERFORMANCE DECLARATION
Species	Radiata pine ( <i>Pinus radiata</i> )
Intended use	For interior use
Density and range of thickness	465 kg/m <sup>3</sup> , 15-19 mm
Reaction to fire	D-s2, do (density: $\geq 390$ kg/m <sup>3</sup> ; minimum thickness total/minimum: $\geq 9/6$ mm)
Emission of formaldehyde	E1
Content of pentachlorophenol	NPD
Release of other dangerous substances	NPD
Water vapor permeability	NPD
Thermal resistance	0,12 W/(m K)
Sound absorption	250 Hz to 500 Hz = 0,1; 1000 Hz to 2000 Hz = 0,3
Biological durability	Class 2, when thermally modified (thermo-D) (according to CEN/TS 15083-1:2005)
Resistance to fixing	NPD





---

Johann Sulling  
General Manager  
Tallinn 20.06.2019