



DECLARATION OF PERFORMANCE

The undersigned, representing
Thermory AS (Lõõtsa 1a, Tallinn, Harju County, Estonia)
and the manufacturing plant in Loo, Harju County, Estonia
hereby declares that the

THERMALLY MODIFIED SOLID WOOD CLADDING AND PANELING WITH “VIVID SILVERED LIGHT GRAY” COATING

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product Regulation system of assessment and verification of constancy of performance: System 3 and is in accordance with the requirements of

EN 14915:2013

„Solid wood paneling and cladding – Characteristics, evaluation of conformity and marking“. Initial type testing report No.01_THERMORY_EN14915

CHARACTERISTIC	PERFORMANCE DECLARATION			HARMONIZED STANDARD
Species	Norway spruce (<i>Picea abies</i>)	Scots pine (<i>Pinus sylvestris</i>)	Radiata pine (<i>Pinus radiata</i>)	
Intended use	For exterior and interior use			
Density and range of thickness	400 kg/m ³ , 18 ≤ mm	435 kg/m ³ , 18 ≤ mm	455 kg/m ³ , 18 ≤ mm	EN 14915:2013
Reaction to fire	D-s2, d0			EN 13501-1:2018
Emission of formaldehyde	E1			EN 14915:2013
Content of pentachlorophenol	NPD			EN 14915:2013
Release of other dangerous substances	NPD			EN 14915:2013
Water vapor permeability	NPD			EN 14915:2013
Thermal resistance	0,12 W/(m K)			EN 14915:2013
Sound absorption	NPD			EN 14915:2013
Biological durability	Class 1, when thermally modified (215 °C, Intense)	Class 2, when thermally modified (215 °C, Intense)	Class 2, when thermally modified (220 °C, Intense)	CEN/TS 15083-1:2005

Gert Zuba
CQO
Tallinn 19.04.2023

