




THERMORY®
LEAVE A LASTING IMPACT



DECLARATION OF PERFORMANCE

No 2023TSRSSv1

Thermory AS (Löötsa 1a, Tallinn, Harju County, Estonia)
and the manufacturing plant in Loo, Harju County, Estonia hereby declares that the

THERMALLY MODIFIED ASH SOLID WOOD CLADDING AND PANELING WITH “SILVER SHIELD” COATING

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product Regulation system of assessment and verification of constancy of performance: System 3 and is in accordance with the requirements of

EN 14915:2013

„Solid wood paneling and cladding – Characteristics, evaluation of conformity and marking“ Initial type testing report No.01_THERMORY_EN14915

CHARACTERISTIC	PERFORMANCE DECLARATION	HARMONIZED STANDARD
Species	Ash (<i>Fraxinus excelsior/americana</i>)	
Intended use	For exterior and interior use	
Density and range of thickness	620 kg/m ³ , 18 ≤ mm	EN 14915:2013
Reaction to fire	D-s2, d0	EN 13501-1:2018
Emission of formaldehyde	E1	EN 14915:2013
Content of pentachlorophenol	NPD	EN 14915:2013
Release of other dangerous substances	NPD	EN 14915:2013
Water vapor permeability	NPD	EN 14915:2013
Thermal resistance	0,13 W/(m K)	EN 14915:2013
Sound absorption	NPD	EN 14915:2013
Biological durability	Class 1, when thermally modified (215 °C, Intense)	EN 113-2:2020

Gert Zuba
CQO
Tallinn 30.10.2023

