



# DECLARATION OF PERFORMANCE

## No 2025VOL-D

The undersigned, representing  
Thermory AS (Löötsa 1a, Tallinn, Harju County, Estonia)  
and the manufacturing plant in Loo, Harju County, Estonia  
hereby declares that the

### THERMALLY MODIFIED SOLID WOOD CLADDING WITH “VIVID OILED LIGHT-D” COATING

#### For exterior use

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product Regulation system of assessment and verification of constancy of performance: System 3 and is in accordance with the requirements of

#### EN 14915:2013

„Solid wood paneling and cladding – Characteristics, evaluation of conformity and marking“.  
Testing Laboratory (Notified body No.2040)  
Classification report No.K2/2025

CHARACTERISTIC	PERFORMANCE DECLARATION			HARMONIZED STANDARD
Species	Norway spruce ( <i>Picea abies</i> )	Scots pine ( <i>Pinus sylvestris</i> )	Radiata pine ( <i>Pinus radiata</i> )	EN 13556:2003
Density and range of thickness	420 - 450 kg/m <sup>3</sup> ; ≥18 mm	400 - 450 kg/m <sup>3</sup> ; ≥18 mm	430 - 450 kg/m <sup>3</sup> ; ≥18 mm	EN 14915:2013
Reaction to fire	D-s2, d0			EN 13501-1:2018
Emission of formaldehyde	E1			EN 14915:2013
Content of pentachlorophenol	NPD			
Release of other dangerous substances	NPD			
Water vapor permeability	NPD			
Thermal conductivity	0,12 W/(m K)			
Sound absorption	NPD			EN 350:2016
Biological durability	Class 1, when thermally modified (215 °C, Intense)	Class 2, when thermally modified (215 °C, Intense)	Class 2, when thermally modified (220 °C, Intense)	

Gert Zuba  
CQO  
Tallinn 15.01.2024